

ORBEA



ORCA M21TEAM-D.

ESTÁ EN ESTOS COLORES:



NEGRO (MATE-BRILLO)



AZUL BONDI (BRILLO)



AZUL MARINO MET - BRIGHT
RED (MATE)

ESPECIFICACIONES Y OPCIONES

CUADRO	Orbea Orca OMR Disc carbon 2020, monocoque construction, tapered 1-1/8" - 1,5", BB 386, powermeter compatible, thru axle 12mm x 142mm rear, thread M12x P1.5, internal cable routing, EC/DC compatible, SP 27,2mm.
HORQUILLA	Orbea Orca OMR Disc carbon fork 2020, full carbon steerer, tapered 1-1/8" - 1,5", carbon dropouts, thru axle 12 x 100mm, thread M12xP1.5
PLATO	SRAM Force Dub 33x46t
DIRECCION	FSA 1-1/8 - 1-1/2" Integrated Carbon Cup ACB Bearings
MANILLAR	OC2 Road, reach 80mm, drop 125mm
POTENCIA	OC2 Road -8º
MANETAS	SRAM Force eTap AXS
FRENO	SRAM Force eTap AXS
PIÑON	SRAM XG-1270 10-28t 12-Speed
CAMBIO	SRAM Force eTAP
DESVIADOR	SRAM Force eTAP
CADENA	SRAM Force 12-Speed
RUEDA	FULCRUM Racing 400 DB
CUBIERTA	Hutchinson Fusion 5 All Season TLR 700x28
PEDALES	N/A
TIJA SILLIN	OC2 27.2 Offset 20
SILLIN	Prologo Dimension T4.0 size143 mm
BATERÍA	SRAM eTap Powerpack
CINTA MANILLAR	Orbea Anti-Slippery/Shock Proof
EJE RUEDA DELANTERO	Orbea Road 12x100mm, thread M12xP1.5
EJE RUEDA TRASERO	Orbea Road 12x142mm, thread M12xP1.5
--	

GEOMETRÍA

TALLA	47	49	51	53	55	57	60
1 - SEAT_TUBE	440	460	480	500	520	540	570
2 - TOP_TUBE	510	522	536	548,8	560	576	590
3 - HEAD_TUBE	104	111	130	148	168	186	213
4 - CHAIN_STAY				414			
5 - BB_HEIGHT	269,5	269,5	269,5	271,5	271,5	271,5	271,5
6 - BB_DROP	72	72	72	70	70	70	70
7 - WHEELBASE	979	983	987	988	999	1009	1023
8 - HEAD_ANGLE	71º	71.5º	72.2º	72.8º	73º	73.2º	73.2º
9 - SEAT_ANGLE	74.5º	74º	73.7º	73.5º	73.5º	73.2º	73.2º
10 - STANDOVER	729	742	758	780	800	817	844
11 - REACH	370	375	380	385	391	398	404
12 - STACK	506	515	533	552	572	590	616
13 - FORK_LENGTH				370			

ERGONOMÍA

TALLA	BIELA	POTENCIA	MANILLAR
47	170	90	400
49	170	100	400
51	170	100	420
53	170	110	420
55	172	110	420
57	172	110	440
60	175	120	440

* La medida del manillar es centro-centro

