

ORBEA



KERAM COMFORT 20.

IN DIESEN FARBEN VORHANDEN:



BLAU



ORANGE-SCHWARZ
(GLÄNZEND)



SILBER-SCHWARZ (SATIN)

TECHNISCHE EIGENSCHAFTEN UND OPTIONEN

RAHMEN	Orbea Keram, compatible 2,8mm tires
GABEL	SR Suntour NEX E-25 63mm Disc
KURBELGARNITUR	FSA Bosch-IG3 E-bike 36t
STEUERSATZ	FSA 1-1/8 - 1-1/2" Integrated
LENKER	Orbea Comfort Riser Alu 660mm Orbea OC-I Riser 740mm
VORBAU	Orbea Black Adjustable Orbea OC-II 90mm
HEBEL	Shimano Deore M6000
BREMSEN	Shimano M315 Hydraulic Disc
RITZEL	Shimano HG50 11-36t 10-Speed
SCHALTWERK	Shimano Deore M6000 GS Shadow Plus
KETTE	KMC X10e
RÄDER	Orbea Black Rock 23c Disc
REIFEN	Kenda K935 1,65" Reflex
PEDALE	VP-615 Black
SATTELSTÜTZE	Orbea 31.6x350mm w/Suspension Orbea OC-I 31.6x400mm
SATTEL	Selle Royal Milo Plus HR Selle Royal Milo Plus DR Selle Royal 2077 DRN
HINTERER GEPÄCKTRÄGER	PORTABULTOS DE ACERO PARA RUEDAS DE 26 Y 28 NEGRO
SCHUTZBLECH	SKS 28" 65mm
VORDERLICHT	Spanninga Kendo 15 lux
RÜCKLICHT	Spanninga Lineo
KETTENSCHUTZ	FSA Bosch IG3 36-38t
FAHRRADSCHLOSS	Axa Solid Plus frame lock + battery down tube lock
FAHRRADSTÄNDER	Yuen I YRA-60B Kickstand
MOTOR	BOSCH Active Plus 25 kmh
AKKU	BOSCH Performance 500Wh
PEDALARM	FSA CK-602 Bosch IG3 170mm
RADNABE	Safety Lock

GEOMETRIE

GRÖßE	S	M	L
1 - SEAT_TUBE	418	450	530
2 - TOP_TUBE	550	570	605
3 - HEAD_TUBE	130	130	150
4 - CHAIN_STAY		481	
5 - BB_HEIGHT	298	305	305
6 - BB_DROP	52,5	63	63
7 - WHEELBASE	1102	1133	1170
8 - HEAD_ANGLE	69°	68°	68°
9 - SEAT_ANGLE		73°	
10 - STANDOVER	792	822	855
11 - REACH	360	374	403
12 - STACK	616	637	656
13 - FORK_LENGTH	490	508	658

ERGONOMIE

GRÖßE	KURBELLÄNGE	VORBRAU	LENKER
S	170	90	660
M	170	90	660
L	170	90	660

* Das Lenkermaß ist Mitte-Mitte

