

ORBEA



KERAM COMFORT 20.

IN DIESEN FARBEN VORHANDEN:



BLAU



ORANGE-SCHWARZ
(GLÄNZEND)



SILBER-SCHWARZ (SATIN)

TECHNISCHE EIGENSCHAFTEN UND OPTIONEN

| | |
|------------------------------|------------------------------------------------------------------------------|
| RAHMEN | Orbea Keram, compatible 2,8mm tires |
| GABEL | SR Suntour NEX E-25 63mm Disc |
| KURBELGARNITUR | FSA Bosch-IG3 E-bike 36t |
| STEUERSATZ | FSA 1-1/8 - 1-1/2" Integrated |
| LENKER | Orbea Comfort Riser Alu 660mm Orbea OC-I Riser 740mm |
| VORBAU | Orbea Black Adjustable Orbea OC-II 90mm |
| HEBEL | Shimano Deore M6000 |
| BREMSEN | Shimano M315 Hydraulic Disc |
| RITZEL | Shimano HG50 11-36t 10-Speed |
| SCHALTWERK | Shimano Deore M6000 GS Shadow Plus |
| KETTE | KMC X10e |
| RÄDER | Orbea Black Rock 23c Disc |
| REIFEN | Kenda K935 1,65" Reflex |
| PEDALE | VP-615 Black |
| SATTELSTÜTZE | Orbea 31.6x350mm w/Suspension Orbea OC-I 31.6x400mm |
| SATTEL | Selle Royal Milo Plus HR Selle Royal Milo Plus DR Selle Royal 2077 DRN |
| HINTERER GEPÄCKTRÄGER | PORTABULTOS DE ACERO PARA RUEDAS DE 26 Y 28 NEGRO |
| SCHUTZBLECH | SKS 28" 65mm |
| VORDERLICHT | Spanninga Kendo 15 lux |
| RÜCKLICHT | Spanninga Lineo |
| KETTENSCHUTZ | FSA Bosch IG3 36-38t |
| FAHRRADSCHLOSS | Axa Solid Plus frame lock + battery down tube lock |
| FAHRRADSTÄNDER | Yuen I YRA-60B Kickstand |
| MOTOR | BOSCH Active Plus 25 kmh |
| AKKU | BOSCH Performance 500Wh |
| PEDALARM | FSA CK-602 Bosch IG3 170mm |
| RADNABE | Safety Lock |

GEOMETRIE

| GRÖßE | S | M | L |
|-------------------------|------|------|------|
| 1 - SEAT_TUBE | 418 | 450 | 530 |
| 2 - TOP_TUBE | 550 | 570 | 605 |
| 3 - HEAD_TUBE | 130 | 130 | 150 |
| 4 - CHAIN_STAY | | 481 | |
| 5 - BB_HEIGHT | 298 | 305 | 305 |
| 6 - BB_DROP | 52,5 | 63 | 63 |
| 7 - WHEELBASE | 1102 | 1133 | 1170 |
| 8 - HEAD_ANGLE | 69° | 68° | 68° |
| 9 - SEAT_ANGLE | | 73° | |
| 10 - STANDOVER | 792 | 822 | 855 |
| 11 - REACH | 360 | 374 | 403 |
| 12 - STACK | 616 | 637 | 656 |
| 13 - FORK_LENGTH | 490 | 508 | 658 |

ERGONOMIE

| GRÖßE | KURBELLÄNGE | VORBRAU | LENKER |
|----------|-------------|---------|--------|
| S | 170 | 90 | 660 |
| M | 170 | 90 | 660 |
| L | 170 | 90 | 660 |

* Das Lenkermaß ist Mitte-Mitte

