

**ORBEA**



## GAIN D31 19.

BESCHIKBAAR IN DEZE KLEUREN:



ORANJE-ZWART (GLOSS)



GRIJS-WIT (DOF-GLOSS)



GRAFJET-ANTRACIET (DOF)

## SPECIFICATIES AND OPTIES

<b>FIETSFRAME</b>	Orbea Gain Hydro, Aluminum 6000 series, Orbea Tube Shaping, Flat Mount Disc Brakes, 135x9 QR, Carrier and Mudguards compatible, max 700x40C, Inner Cable routing, Ebikemotion X35 specific, integrated battery, in
<b>VORK</b>	Speed 400mm Carbon Flat mount
<b>CRANKSET</b>	SRAM Rival 40t
<b>BALHOOFDLAGER PERB</b>	1-1/8" Semi-Integrated
<b>STUUR</b>	FSA Gossamer Compact
<b>STUURPEN</b>	Orbea OC-III
<b>HENDELS</b>	SRAM Rival
<b>REMMEN</b>	SRAM Rival Hydraulic
<b>KETTINGWIEL</b>	SRAM Rival PG-1130 11-36t 11-Speed
<b>ACHTERDERAILLEUR</b>	SRAM Rival 1 X-Horizon
<b>KETTING</b>	KMC e11 Turbo Silver
<b>WIELEN</b>	Ready GR
<b>BANDEN</b>	Schwalbe G-ONE Allround, 40-622, Black, Folding Hutchinson Fusion 5 All Season TLR 700x28
<b>TRAPPERS</b>	N/A
<b>ZADELPEN</b>	FSA SL-K SB20 27.2x350mm Di2 compatible
<b>ZADEL</b>	Prologo Kappa Space STN size 147mm
<b>MOTOR</b>	Ebikemotion X35 25kmh
<b>BATTERIJ</b>	Ebikemotion 36V/6.9A
<b>HANDLEBAR PLUGS</b>	Velo Anti-Slippery/Shock Proof
<b>CHARGER</b>	Ebikemotion X35
<b>REMOTE1</b>	Ebikemotion iWoc ONE
--	Left Road

## GEOMETRIE

MAAT	XS	S	M	L	XL
<b>1 - SEAT_TUBE</b>	460	510	555	585	610
<b>2 - TOP_TUBE</b>	522	546	560	574	595
<b>3 - HEAD_TUBE</b>	109	127	150	176	203
<b>4 - CHAIN_STAY</b>			430		
<b>5 - BB_HEIGHT</b>	281	281	283	283	285
<b>6 - BB_DROP</b>	70	70	68	68	66
<b>7 - WHEELBASE</b>	1016	1022	1037	1051	1067
<b>8 - HEAD_ANGLE</b>	71°	72°	72°	72°	72.3°
<b>9 - SEAT_ANGLE</b>	75°	74°	74°	74°	73.5°
<b>10 - STANDOVER</b>	754	782	815	829	876
<b>11 - REACH</b>	378	387	395	402	410
<b>12 - STACK</b>	535	555	575	600	625
<b>13 - FORK_LENGTH</b>			400		
<b>14 - OFFSET</b>			51		

## ERGONOMIE

MAAT	CRANK	STEM	HANDLEBAR
<b>47</b>	170	90	400
<b>49</b>	170	100	400
<b>51</b>	170	100	420
<b>53</b>	172.5	110	420
<b>55</b>	172.5	110	420
<b>57</b>	172.5	110	440
<b>60</b>	175	120	440

\* De maat van het fietsstuur is centre-centre

