

**ORBEA**



## GAIN MID 19.

BESCHIKBAAR IN DEZE KLEUREN:



ZWART (DOF) / GRIJS  
(GLOSS)



ORANJE-GEEL (GLOSS)



BRIGHT RED-BLAUW (DOF)



BLAUW ORBEA-WI (DOF)

## SPECIFICATIES AND OPTIES

<b>FIETSFRAME</b>	Orbea Gain Carbon, Monocoque carbon structure, Flat Mount Disc Brakes, 135x9 QR, max 700x40C, Inner Cable routing, Ebikemotion X35 specific, integrated battery, integrated sensor, Iwoc One compatible
<b>VORK</b>	Gain Carbon Flat mount
<b>CRANKSET</b>	Shimano Dura-Ace 9100 34x50t
<b>BALHOOFDLAGER PERB</b>	FSA 1-1/8 - 1-1/2" Integrated Carbon Cup ACB Bearings
<b>STUUR</b>	FSA K-Force Compact
<b>STUURPEN</b>	FSA OS-99 CSI
<b>HENDELS</b>	Shimano R9120
<b>REMMEN</b>	Shimano R9170 Hydraulic Disc
<b>KETTINGWIEL</b>	Shimano Dura-Ace 9100 11-30t 11-Speed Shimano Dura-Ace R9100 11-28t 11-Speed
<b>ACHTERDERAILLEUR</b>	Shimano Dura-Ace 9100
<b>VOORDERAILLEUR</b>	Shimano Dura-Ace 9100
<b>KETTING</b>	Shimano HG 901
<b>WIELEN</b>	Mavic Cosmic Pro Carbon Disc UST
<b>BANDEN</b>	Yksion Pro UST 28 Hutchinson Fusion 5 All Season TLR 700x25
<b>TRAPPERS</b>	N/A
<b>ZADELPEN</b>	FSA K-Force SB25 31.6x350mm Di2 compatible
<b>ZADEL</b>	Prologo Nago Evo Space Tirox size 141mm Prologo Kappa Space STN size 147mm
<b>MOTOR</b>	Ebikemotion X35 25kmh
<b>BATTERIJ</b>	Ebikemotion 36V/6.9A
<b>HANDLEBAR PLUGS</b>	Velo Anti-Slippery/Shock Proof
<b>CHARGER</b>	Ebikemotion X35
<b>REMOTE1</b>	Ebikemotion iWoc ONE
--	
	Left Road

## GEOMETRIE

MAAT	XS	S	M	L	XL
<b>1 - SEAT_TUBE</b>	470	510	540	555	570
<b>2 - TOP_TUBE</b>	517.9	528	549.5	568.8	591
<b>3 - HEAD_TUBE</b>	98.7	115	130	142	155
<b>4 - CHAIN_STAY</b>			435		
<b>5 - BB_HEIGHT</b>			67		
<b>6 - BB_DROP</b>			272		
<b>7 - WHEELBASE</b>	1005.6	1016	1024.5	1034.9	1051
<b>8 - HEAD_ANGLE</b>	69.5°	69.5°	67.1°	71.9°	72.5°
<b>9 - SEAT_ANGLE</b>			72.4°		
<b>10 - STANDOVER</b>	715	741	765	778	793
<b>11 - REACH</b>	355	360.2	375.4	390	407.6
<b>12 - STACK</b>	515	530.2	550.1	565	579.5
<b>13 - FORK_LENGTH</b>			395		
<b>14 - OFFSET</b>			50		

## ERGONOMIE

MAAT	CRANK	STEM	HANDLEBAR
<b>47</b>	170	90	400
<b>49</b>	170	100	400
<b>51</b>	170	100	420
<b>53</b>	172.5	110	420
<b>55</b>	172.5	110	420
<b>57</b>	172.5	110	440
<b>60</b>	175	120	440

\* De maat van het fietsstuur is centre-centre

