

ORBEA



ORCA AERO OMR 19.

BESCHIKBAAR IN DEZE KLEUREN:



STAAL ZWART (GLOSS-MAT)



ZWART-ROOD (DOF)



ROOD-ZWART (DOF)



BLAUW (GLOSS)



PAREL-ZILVER (DOF)

SPECIFICATIES AND OPTIES

FIETSFRAME	Orbea Orca Aero carbon OMR, monocoque construction, tapered 1-1/8" - 1,5", BB 386mm, powermeter compatible, internal cable routing, EC/DC compatible.
VORK	Orca Aero OMR carbon fork, full carbon steerer, tapered 1-1/8" - 1,5", carbon dropouts
BALHOOFDLAGER PERB	FSA 1-1/8 - 1-1/2" Integrated Carbon Cup ACB Bearings
STURPEN	Orbea OC-III
ZADELPEN	Orbea Aero OMR
COMPONENTE EN BLANCO (WEB)	

GEOMETRIE

MAAT	47	49	51	53	55	57	60	
1 - SEAT_TUBE	450	465	490	515	535	555	580	
2 - TOP_TUBE	509	521	534	547	559	575	588	
3 - HEAD_TUBE	100	108	124	144	163	181	208	
4 - CHAIN_STAY								408
5 - BB_HEIGHT								269.5
6 - BB_DROP	72	72	72	70	70	70	70	
7 - WHEELBASE	970	974	978	980	991	1000	1014	
8 - HEAD_ANGLE	71	71.5	72.2	72.8	73	73.2	73.2	
9 - SEAT_ANGLE	74.5	74	73.7	73.5	73.5	73.2	73.2	
10 - STANDOVER	740	752	773	797	816	834	857	
11 - REACH	370	375	380	385	391	398	404	
12 - STACK	501	510	528	548	567	585	611	
13 - FORK_LENGTH								370
14 - OFFSET	48MM	48MM	48MM	43MM	43MM	43MM	43MM	

