

ORBEA



ALMA MIO.

SE TROUVE DANS CES COULEURS:



ANTHRACITE-NOIR
(BRILLANT)



NOIR-ORANGE (MAT)



MENTHE-NOIR (BRILLANT)



BRILLANT ROUGE-BLEU (MAT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Alma Carbon OMR Boost Taper PF DCR
FOURCHE	Fox 32 Float SC Factory 100 FIT4 Remote-Adj Push-Unlock QR15x110 Kashima
	Orbea Spirit Rigid Carbon 15x110
PLATEAU DE PEDALIER	Shimano XTR M9100 34t
DIRECTION	Acros Alloy 1-1/8 - 1-1/2" Integrated
CINTRE	FSA SL-K Flat 740mm
	FSA K-Force Flat 760mm Kit (Bar+Stem+Seat post)
POTENCE	FSA SL-K
MANETTES	Shimano XTR M9100
FREINS	Shimano XT M8100 Hydraulic Disc
	Shimano XTR M9100 Hydraulic Disc
PIGNON	Shimano XT M8100 10-51t 12-Speed
DERAILLEUR ARRIÈRE	Shimano XTR M9100 SGS Shadow Plus
CHAINE	Shimano M8100
ROUES	DT Swiss XR-1650 Spline 25c TLR CL, Star Ratchet, Boost
	DT Swiss XRC 1200 Spline 25c CL TL F-15/110mm R-12/148mm
PNEUS	Maxxis Ikon 2.20" FB 120 TPI 3C Exo TR
PEDALE	N/A
TIGE SELLE	FSA SL-K SB0 27.2x400mm Di2 compatible
SELLE	Selle Italia X-LR Ti Flow
	Selle Italia X-LR Kit Carbonio L Black
BLOCAGE AVANT	Fox Kabolt Boost

GÉOMÉTRIE

TAILLE	S-27.5"	M-27.5"	S-29"	M-29"	L-29"	XL-29"
1 - SEAT_TUBE	400	445	400	445	483	533
2 - TOP_TUBE	550	582	557	588	616	640
3 - HEAD_TUBE	95	105	90	95	105	120
4 - CHAIN_STAY	420	420	430	430	430	430
5 - BB_HEIGHT	312	312	309	309	309	309
6 - BB_DROP	43	43	61	61	61	61
7 - WHEELBASE	1045	1078	1061	1092	1121	1146
8 - HEAD_ANGLE	69.3°	69.3°	69.5°	69.5°	69.5°	69.5°
9 - SEAT_ANGLE	73.5°					
10 - STANDOVER	716	735	715	735	741	802
11 - REACH	380	409	380	409	435	455
12 - STACK	573	583	597	602	611	625
13 - FORK_LENGTH	487,7	487,7	500,8	500,8	500,8	500,8
14 - OFFSET	44					

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S-27	170	70	740
S-29	170	70	740
M-27	175	70	740
M-29	175	70	740
L-29	175	90	740
XL-29	175	110	740

* La dimension du guidon est centre-centre

