

ORBEA



ALMA M50.

SE TROUVE DANS CES COULEURS:



GRAPHITE NOIR (MAT) /
NOIR (BRILLANT)



ROUGE-NOIR (BRILLANT)



VERT-OR (MAT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Alma Carbon OMP 2018 Boost Press Fit Taper
FOURCHE	RockShox Judy Silver TK Remote Solo Air 100 QR15x110 Boost RockShox Reba RL 100 Air QR15x110 Boost
PLATEAU DE PEDALIER	Shimano MT610 32t
DIRECTION	Acros Alloy 1-1/8 - 1-1/2" Integrated
CINTRE	OC1 Flat 31.8mm 740mm
POTENCE	Alloy 31.8mm interface 7°
MANETTES	Shimano SLX M7100
FREINS	Shimano MT201 Hydraulic Disc Shimano MT501 BR500 Hydraulic Disc
PIGNON	Shimano SLX M7100 10-51t 12-Speed
DERAILLEUR ARRIÈRE	Shimano SLX M7100 SGS Shadow Plus
CHAINE	Shimano M7100
ROUES	Mach1 Kl maxx 23c Tubeless Ready DT Swiss X 1900 Spline 25c CL TL 15/110mm + Maxxis TLR Tires
PNEUS	Maxxis Ikon 2.20" FB 60 TPI Dual Maxxis Ikon 2.20" FB 120 TPI 3C Exo TR
PEDALE	N/A
TIGE SELLE	Alloy forge head 27.2 Offset 0
SELLE	Selle Royal Seta Sport Selle Italia SL X-Cross Flow Selle Italia X3 Lady Boost
--	

GÉOMÉTRIE

TAILLE	S-27.5"	M-27.5"	S-29"	M-29"	L-29"	XL-29"
1 - SEAT_TUBE	400	445	400	445	483	533
2 - TOP_TUBE	550	582	557	588	616	640
3 - HEAD_TUBE	105	115	95	105	115	130
4 - CHAIN_STAY	425	425	436	436	436	436
5 - BB_HEIGHT	312	312	309	309	309	309
6 - BB_DROP	43	43	61	61	61	61
7 - WHEELBASE	1045	1078	1073	1092	1121	1146
8 - HEAD_ANGLE	69°					
9 - SEAT_ANGLE	73.5°					
10 - STANDOVER	716	735	715	735	741	802
11 - REACH	380	409	380	409	435	455
12 - STACK	581	590	600	609	618	632
13 - FORK_LENGTH	487,7	487,7	500,8	500,8	500,8	500,8
14 - OFFSET	44					

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S-27	170	70	740
S-29	170	70	740
M-27	175	70	740
M-29	175	70	740
L-29	175	90	740
XL-29	175	110	740

* La dimension du guidon est centre-centre

