

ORBEA



WILD FS 10 29S 19.

IN DIESEN FARBEN VORHANDEN:



HELLROT-SCHWARZ
(MATT-GLÄNZEND)



VIOLETT-SCHWARZ (MATT)

TECHNISCHE EIGENSCHAFTEN UND OPTIONEN

RAHMEN	ORBEA WILD Full Suspension 2019 Hydroformed Alloy 140mm Travel Boost 12X148 for Shimano E8000/7000
FEDERUNG	Fox Float DPS Factory 3-Position Adjust Evol Kashima custom tune 200x51mm
GABEL	Fox 34 Float Factory 140 FIT4 3-Pos-Adj QR15x110 Kashima E-Bike Optimized
	Fox 36 Float Factory 150 Grip2 RC2 QR15x110 Kashima
KURBEL	SRAM X-SYNC Eagle 34T
PEDALARM	Miranda Delta 155mm
STEUERSATZ	Acros Alloy 1-1/8 - 1-1/2" Integrated
LENKER	Race Face Aeffect 35 20mm Rise 780mm
VORBAU	Race Face Aeffect 35mm interface
HEBEL	SRAM XX1 Eagle Single click
BREMSEN	SRAM Code RSC Hydraulic Disc
KASSETTE	SRAM NX PG-1230 Eagle 11-50t 12-Speed
SCHALTWERK	SRAM XX1 Eagle Gold
KETTE	SRAM XX1 Eagle 12-Speed
FELGE	DT H-1700 Spline 30c TLR 15/110mm IS (6-bolt)
REIFEN	Kenda 1211E Nevegal 2 29x2.4" 60TPI TLR (E-MTB specific)
	Kenda 1201E Hellkat/1211E Nevegal 29X2,6 60 TPI TLR (E-MTB)
PEDALE	VP-537 Black
SATTELSTÜTZE	Race Face Aeffect Dropper 31,6x385/125mm Crank brothers Highline 31,6x425/150mm
SATTEL	Selle Royal 2077 DRN
FAHRRADSCHLOSS	Abus battery down tube lock
KETTENFÜHRUNG	Etherteen E8000
MOTOR	Shimano Steps DU-E8000 25kmh
AKKU	Shimano Steps E8010
DISPLAY	Shimano Steps SC-E8000
ZURÜCK RADNABE	
LADEGERÄT	Shimano Steps E6002 Shimano Steps E6000
REMOTE1	Shimano E8000 switch unit for assist
--	

GEOMETRIE

GRÖßE	S	M	L	XL
1 - SEAT_TUBE	390	430	470	510
2 - TOP_TUBE	565	581	610	639
3 - HEAD_TUBE	115	128	143	159
4 - CHAIN_STAY			450	
5 - BB_HEIGHT			337.5	
6 - BB_DROP			30	
7 - WHEELBASE	1132	1152	1183	1215
8 - HEAD_ANGLE			67	
9 - SEAT_ANGLE			74°	
10 - STANDOVER	715	745	765	790
11 - REACH	385	400	425	450
12 - STACK	620	632	646	661
13 - FORK_LENGTH			545	
14 - OFFSET			44	

ERGONOMIE

GRÖßE	KURBELLÄNGE	VORBRAU	LENKER
S	152	50	780
M	152	50	780
L	152	50	780
XL	152	50	780

* Das Lenkermaß ist Mitte-Mitte

