

**ORBEA**

## WILD FS 20 27S 19.



IN DIESEN FARBEN VORHANDEN:



HELLROT-SCHWARZ  
(MATT-GLÄNZEND)



VIOLETT-SCHWARZ (MATT)

## TECHNISCHE EIGENSCHAFTEN UND OPTIONEN

<b>RAHMEN</b>	ORBEA WILD Full Suspension 2019 Hydroformed Alloy 140mm Travel Boost 12X148 for Shimano E8000/7000
<b>FEDERUNG</b>	Fox Float DPS Performance 3-Position Evol custom tune 200x51mm
<b>GABEL</b>	Fox 34 Float Performance 140 3-Position QR15x110 E-Bike Optimized
	Fox 36 Float Performance 150 Grip2 RC2 QR15x110
<b>KURBEL</b>	Shimano E80 34t
<b>PEDALARM</b>	Miranda Delta 155mm
<b>STEUERSATZ</b>	Acros Alloy 1-1/8 - 1-1/2" Integrated
<b>LENKER</b>	Race Face Ride 35 20mm Rise 760mm
<b>VORBAU</b>	Race Face Ride 35mm interface
<b>HEBEL</b>	Shimano XT M8000 I-Spec
<b>BREMSEN</b>	Shimano XT M8020 Hydraulic Disc
<b>KASSETTE</b>	Sun Race 11-46t 11-Speed
<b>SCHALTWERK</b>	Shimano XT M8000 GS Shadow Plus Direct Mount
<b>KETTE</b>	KMC e11 Turbo Silver
<b>FELGE</b>	DT H-1900 Spline 35c TLR 15/110mm IS (6-bolt)
	DT H-1700 Spline 30c TLR 15/110mm IS (6-bolt)
<b>REIFEN</b>	Kenda 1184A Havok 27,5x2,8" 120TPI TLR (E-MTB specific)
<b>PEDALE</b>	VP-537 Black
<b>SATTELSTÜTZE</b>	Race Face Aeffect Dropper 31.6x385/125mm
	Crank brothers Highline 31,6x425/150mm
<b>SATTEL</b>	Selle Royal 2077 DRN
<b>FAHRRADSCHLOSS</b>	Abus battery down tube lock
<b>KETTENFÜHRUNG</b>	Etherteen E8000
<b>MOTOR</b>	Shimano Steps DU-E8000 25kmh
<b>AKKU</b>	Shimano Steps E8010
<b>DISPLAY</b>	Shimano Steps SC-E8000
<b>ZURÜCK RADNABE</b>	
<b>LADEGERÄT</b>	Shimano Steps E6002
	Shimano Steps E6000
<b>REMOTE1</b>	Shimano E8000 switch unit for assist
--	

## GEOMETRIE

GRÖßE	S	M	L	XL
<b>1 - SEAT_TUBE</b>	390	430	470	510
<b>2 - TOP_TUBE</b>	565	581	610	639
<b>3 - HEAD_TUBE</b>	115	128	143	159
<b>4 - CHAIN_STAY</b>			450	
<b>5 - BB_HEIGHT</b>			337.5	
<b>6 - BB_DROP</b>			30	
<b>7 - WHEELBASE</b>	1132	1152	1183	1215
<b>8 - HEAD_ANGLE</b>			67	
<b>9 - SEAT_ANGLE</b>			74°	
<b>10 - STANDOVER</b>	715	745	765	790
<b>11 - REACH</b>	385	400	425	450
<b>12 - STACK</b>	620	632	646	661
<b>13 - FORK_LENGTH</b>			545	
<b>14 - OFFSET</b>			44	

## ERGONOMIE

GRÖßE	KURBELLÄNGE	VORBRAU	LENKER
<b>S</b>	152	50	760
<b>M</b>	152	50	760
<b>L</b>	152	50	760
<b>XL</b>	152	50	760

\* Das Lenkermaß ist Mitte-Mitte

