

ORBEA



OIZ M-LTD 19.

ESTÁ EN ESTOS COLORES:



AZUL INDIGO / BRIGHT RED
(MATE)



NARANJA-GRAFITO (MATE)



MENTA-NEGRO (BRILLO)

ESPECIFICACIONES Y OPCIONES

CUADRO	Orbea Oiz Carbon OMR 2019 Boost PF Taper UFO2 I-Line
AMORTIGUADOR	Fox i-line DPS Factory Remote Push-Unlock Evol custom tune190x40mm
HORQUILLA	Fox 32 Float SC Factory 100 FIT4 Remote-Adj Push-Unlock QR15x110 Kashima
	TR Suspension Pack 120mm Front/Rear
PLATO	SRAM XX1 Eagle Dub Gold Boost 34t
	Rotor QX1 DM Sram 32t Chainring (EXTRA)
	Rotor QX1 DM Sram 34t Chainring (EXTRA)
DIRECCION	ACROS 1-1/8 - 1-1/2" Integrated
MANILLAR	FSA K-Force Flat 760mm Di2 compatible
POTENCIA	FSA K-Force OS-100 CSI
MANETAS	SRAM XX1 Eagle Gold
FRENO	SRAM Ultimate Carbon Gold Hydraulic Disc
	Shimano XTR M9100 Hydraulic Disc
PIÑON	SRAM XX1 XG-1299 Eagle 10-50t 12-Speed
CAMBIO	SRAM XX1 Eagle Gold
CADENA	SRAM XX1 Eagle 12-Speed Gold
RUEDA	Mavic Crossmax Pro Carbon TL 6-Bolt
CUBIERTA	Maxxis Ikon 2.20" TLR 120 TPI 3C Exo
	Maxxis Forekaster 2.35" TLR (F) / Ardent Race 2.2" TLR (R)
PEDALES	N/A
TIJA SILLIN	FSA K-Force Light SB0 31,6x400mm Di2 compatible
	Race Face Aeffect Dropper 31.6x385/125mm
SILLIN	Selle Italia X-LR Kit Carbonio S
CIERRE RUEDA TRASERO	Fox Kabolt Boost

GEOMETRÍA

TALLA	S-27 (XC)	S (XC)	M (XC)	L (XC)	XL (XC)	-	S-27 (TR)	S (TR)	M (TR)	L (TR)	XL (TR)
1 - SEAT_TUBE	405	405	432	470	520	-	405	405	432	470	520
2 - TOP_TUBE	557	564	593	617	641	-	559	567	596	619	643
3 - HEAD_TUBE	95	90	95	105	120	-	95	90	95	105	120
4 - CHAIN_STAY	425	435	435	435	435	-	425	435	435	435	435
5 - BB_HEIGHT	328	327	327	327	327	-	336	334	334	334	334
6 - BB_DROP	29	47	47	47	47	-	21	40	40	40	40
7 - WHEELBASE	1081	1094	1123	1148	1173	-	1088	1101	1131	1155	1181
8 - HEAD_ANGLE	69	69	69	69	69	-	68	68	68	68	68
9 - SEAT_ANGLE	75	75	75	75	75	-	74	74	74	74	74
10 - STANDOVER	715	717	732	742	749	-	722	724	739	749	756
11 - REACH	407	407	435	456	476	-	397	387	425	446	466
12 - STACK	558	586	591	600	614	-	565	593	598	608	622
13 - FORK_LENGTH	488	504	504	504	504	-	508	524	524	524	524
14 - OFFSET	44	44	44	44	44	-	44	44	44	44	44

ERGONOMÍA

TALLA	BIELA	POTENCIA	MANILLAR
S-27	170	70	760
S-29	170	70	760
M-29	170	70	760
L-29	175	90	760
XL-29	175	110	760

* La medida del manillar es centro-centro

