

ORBEA



VECTOR 20.

ESTÁ EN ESTOS COLORES:



NEGRO (MATE-BRILLO)



VERDE (MATE-BRILLO)



BRIGHT RED-NEGRO
(MATE-BRILLO)



AZULGRIS (MATE-BRILLO)

ESPECIFICACIONES Y OPCIONES

CUADRO	Orbea Urban Speed, Aluminium 6000, Orbea Tube Shaping, Flat Mount Disc Brake, 135x9 QR, Carrier and Mudguard compatible, max 700x40C, Inner Cable routing,
HORQUILLA	Speed 400mm Carbon Flat mount
PLATO	Prowheel 32x48 Steel Custom logo
	Shimano Sora 30x39x50
DIRECCION	1-1/8" Semi-Integrated
MANILLAR	Alloy 31.8mm Riser 640mm
POTENCIA	Alloy 31.8mm interface 7º
MANETAS	Shimano Sora
FRENO	Shimano MT200 Hydraulic Disc
PIÑON	Shimano HG400 11-34t 9-Speed
CAMBIO	Shimano Sora 3000GS
DESVIADOR	Shimano Sora 3000
CADENA	Shimano HG53 9-Speed
RUEDA	Orbea Airline Corsa Disc 700X19c
CUBIERTA	Kenda K1098 700x32 Reflective Tape
	Kenda K1098 700x28C Reflective type + Puncture protection
PEDALES	N/A
TIJA SILLIN	Alloy 27.2 Offset 0
SILLIN	Selle Royal Asphalt GR
GUARDABARROS	SKS EDGE Alloy + Side Bag Carrier + Lights (F-Kendo/R-Lineo)
SOPORTE CICLO	Ursus Mooi rear adjustable

GEOMETRÍA

TALLA	XS	S	M	L	XL
1 - SEAT_TUBE	430	480	525	555	580
2 - TOP_TUBE	521	546	559	580	601
3 - HEAD_TUBE	109	127	150	170	200
4 - CHAIN_STAY			435		
5 - BB_HEIGHT	281	281	283	283	285
6 - BB_DROP	70	70	68	68	66
7 - WHEELBASE	1021	1037	1052	1063	1075
8 - HEAD_ANGLE	71	71	71	71,5	72
9 - SEAT_ANGLE	75	74	74	73,5	73
10 - STANDOVER	738	768	800	824	852
11 - REACH	378	388	395	405	410
12 - STACK	535	552	571	592	625
13 - FORK_LENGTH			400		
14 - OFFSET			51		

ERGONOMÍA

TALLA	BIELA	POTENCIA	MANILLAR
XS	170	90	640
S	170	90	640
M	170	90	640
L	172	90	640
XL	175	90	640

* La medida del manillar es centro-centro

