

ORBEA



ALMA M-LTD 27 - 2016.

SE TROUVE DANS CES COULEURS:



BLANC-NOIR (BRILLANT)



ROUGE-BLEU (SATIN)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Monocoque Race Carbon. Patented 4x4 evo construction. DCR Internal cable routing. XC racing geometry. Tapered Head tube. PF92 Press fit. Direct post mount disc brake. Di2 Ready.
FOURCHE	Fox 32 Float Factory 100 IRD electronic 3-Position Remote QR15 Kashima
PLATEAU DE PEDALIER	Shimano XTR M9000 26x36t
	Shimano XTR M9000 28x38t
DIRECTION	FSA 1-1/8 - 1-1/2" Integrated
CINTRE	FSA K-Force Flat 700mm Di2 ready
POTENCE	FSA OS-99 CSI
MANETTES	Shimano XTR Di2 M9000
FREINS	Shimano XTR Race M9000 Hydraulic Disc
PIGNON	Shimano XTR M9001 11-40t 11-Speed
DERAILLEUR ARRIÈRE	Shimano XTR Di2 GS Shadow Plus
DERAILLEUR AVANT	Shimano XTR Di2 M970 34-38t
CHAINE	Shimano HG900
ROUES	Mavic Crossmax SL Pro TL 6-Bolt
PNEUS	Maxxis Ikon 2.20" TLR 120 TPI 3C Exo
	Maxxis Ardent 2,25" TLR Exo (29":Ardent Race 2,20")
PEDALE	N/A
TIGE SELLE	FSA K-Force Light SB0 27.2x400mm Di2
SELLE	Selle Italia SLR XC Gel Flow
ÉCRAN	Shimano XTR Di2

GÉOMÉTRIE

TAILLE	S - 27.5"	M - 27.5"	L - 27.5"	M - 29"	L - 29"	XL - 29"
1 - SEAT_TUBE	400	445	483	445	483	533
2 - TOP_TUBE	552	583	606	591	613	638
3 - HEAD_TUBE	95	105	115	100	110	125
4 - CHAIN_STAY	423	423	423	436	436	436
5 - BB_HEIGHT	313	313	313	310	310	310
6 - BB_DROP	42	42	42	60	60	60
7 - WHEELBASE	1038	1070	1093	1084	1106	1132
8 - HEAD_ANGLE	70,5°					
9 - SEAT_ANGLE	73,5°	73,5°	73,2°	73,5°	73,5°	73,5°
10 - STANDOVER	720	747	775	747	777	820
11 - REACH	380	409	429	409	423	449
12 - STACK	577	587	596	611	621	635
13 - FORK_LENGTH	489	489	489	501	501	501

ERGONOMIE



TAILLE	BIELLE	POTENCE	CINTRE
S - 27.5"	170	80	700
M - 27.5"	175	80	700
L - 27.5"	175	90	700
M - 29"	175	80	700
L - 29"	175	90	700
XL - 29"	175	110	700

* La dimension du guidon est centre-centre