



ESPECIFICACIONES Y OPCIONES

CUADRO	Orbea Oiz Carbon OMX, Fiberlink, Boost, BSA, SIC, UFO, I-line shock
AMORTIGUADOR	Fox i-line DPS Factory 120mm Remote Push-Unlock Evol Kashima custom tune 190x45mm
HORQUILLA	Fox 34 Float SC Factory 120 FIT4 Remote-Adj Push-Unlock QR15x110
PLATO/BIELA	Shimano XT M8120 32t
DIRECCION	Alloy 1-1/2", Black Oxidated Bearing
MANILLAR	Low Stack Headset Cup
	OC MP10 Mountain Performance Carbon, Width 760, Sweep 9
	OC MC10 CB SL, Rise 20, 800mm (bar) + MC10, 0º, 40mm (stem)
	OC MC10 CB SL, Rise 20, 800mm (bar) + MC10, 0º, 50mm (stem)
POTENCIA	OC Mountain Performance MP10 Alu SL, -10º
MANETAS	Shimano XT M8100 I-Spec EV
FRENO	Shimano XT M8100 Hydraulic Disc
	Shimano XTR M9100 Hydraulic Disc
PIÑON	Shimano CS-M8100 10-51t 12-Speed
CAMBIO	Shimano XTR M9100 SGS Shadow Plus
CADENA	Shimano M8100
RUEDA	Oquo Mountain Performance MP30TEAM, carbon hookless rim, DT350 CL hub, Shimano Micro Spline freehub, 30mm internal width, Sapim D-Sprint spokes, 29"
	OQUO Mountain Performance MP30LTD Carbon CL
CUBIERTA	Maxxis Rekon Race 2.40" WT 120 TPI Exo TLR
	Maxxis Dissector 2.40" 3CMax Exo(F) / Rekon 2.40" Dual Exo
TIJA SILLIN	OC Mountain Control MC20, 31.6mm, Dropper
	OC Mountain Control MC20, 31.6mm, Dropper, Travel 125mm
	OC Mountain Control MC20, 31.6mm, Dropper, Travel 150mm
	OC Mountain Control MC20, 31.6mm, Dropper, Travel 170mm
	Fox Transfer Factory Kashima Dropper 31.6x363,5/125mm
SILLIN	Fox Transfer Factory Kashima Dropper 31.6x418,3/150mm
	Fox Transfer SL Factory Kashima Dropper 31.6x380/100mm
	Fox Transfer SL Factory Kashima Dropper XL 31.6x430/100mm
	Selle Italia SLR Boost Fill Titanium Rail 316 Ø7 mm
EJE RUEDA DELANTERO	Women Kit: OC Grips 29mm & Selle Italia SLR Boost SuperFlow
	Selle Italia SLR Boost Fill Carbon Rail Ø7x9 mm
	N/A
BLOQUEO REMOTO	Fox Kabolt Boost
	OC Squidlock MP20 Remote, Dropper, Suspension 3 Pos

OIZ M-PRO 2023.

ESTÁ EN ESTOS COLORES:



DIGITAL LAVENDER (GLOSS)-
CARBON RAW (MATT)




TANZANITE CARBON
VIEW-CARBON RAW (MATT)



CARBON RAW (MATT)

GEOMETRÍA

TALLA	S	M	L	XL
1 - SEAT_TUBE	405	432	460	510
2 - TOP_TUBE	575	598	623	650
3 - HEAD_TUBE	90	90	100	115
4 - CHAIN_STAY	432			
5 - BB_HEIGHT	333			
6 - BB_DROP	42			
7 - WHEELBASE	1138	1163	1189	1219
8 - HEAD_ANGLE	67º			
9 - SEAT_ANGLE	76.5º			
10 - STANDOVER	731	741	741	750
11 - REACH	425	450	472	496
12 - STACK	596	596	606	619
13 - FORK_LENGTH	531			
14 - OFFSET	44			



ERGONOMÍA

TALLA	BIELA	POTENCIA	MANILLAR	TIJA TELESCÓPICA
S	170	60	760	390/125
M	175	75	760	390/125
L	175	75	760	440/150
XL	175	90	760	440/150

* La medida del manillar es centro-centro

BIELETA	
OTROS	otros